

IDEAL ROUGHCAST

PRODUCT DESCRIPTION AND USES

Ideal Roughcast is a textured Acrylic emulsion-based coating which offers a tough, durable and attractive finish. It is based on 100% pure acrylic emulsion resin. It is suitable for use in new and previously painted plaster, cement rendering, concrete block, stone etc. The roughcast formulation incorporates a versatile fungicide and algacide to combat mould and algae growth both in the can and on the wall.

Advantages.

- Breathes out trapped moisture.
- It has fungicidal resistance.
- Bridges hair-line cracks.
- Its high film thickness disguises minor surface imperfections.

SURFACE PREPARATION

New walls

Ensure surface is clean dry and clear. Apply one coat of Ideal Roughcast using stainless steel trowel followed by a special plastic trowel to attain desired design.

Previously painted surfaces

On previously painted surfaces any deteriorated coats of old paint should be removed completely by scraping and wire brushing and any large cracks should be filled with a hard filler or cement and allowed to dry prior to applying Ideal Roughcast. The desired texture depends on the size of marble grit used.

FINISH

Matt, high build, textured.

APPLICATION

Ideal Roughcast is supplied ready for application and as such requires no more addition of water for thinning. Use a stainless-steel trowel for application and for finishing use a special plastic trowel or comb to create final textured design for e.g. vertical, circular, horizontal and should be washed immediately with water after application.

Ideal Roughcast may be applied to give a coarse textured pattern or a fine textured pattern depending on the client's choice.

Ideal Roughcast usually comes in white colour after which either Ideal All-Weather Guard/Ideal All-Weather Guard Ultra or Silex Ultra Exterior paint of the desired colour can be applied by brush on top after 24 hours.

THINNING AND MIXING

Not to be thinned. Ready for use.

EQUIPMENT CLEANING

Clean trowel with water immediately after use.

DRYING TIME

Ideal Roughcast is touch dry after 2 hours, hard dry after 24 hours.

COLOUR RANGE

Ideal Roughcast is supplied in white and can then be overcoated with two coats to the shade of choice with Ideal All-Weather Guard/Ideal All-Weather Guard Ultra or Silex Ultra Exterior paint

SPREADING CAPACITY

3mm – 3.5kg per m²

2mm – 3kg per m²

Smooth – 2.5kg per m²

PACK SIZES

30 kgs

NOTE:

1. Ideal Paints provide a **Supply and Apply Service** for this product.
2. Roughcast being a pure acrylic emulsion-based texture gives a higher bonding capacity compared to a cement-based product.