

IDEAL EGGSHELL ENAMEL

PRODUCT DESCRIPTION AND USES.

Ideal Eggshell Enamel is a semi-gloss alkyd resin based paint finish designed to use on walls and ceilings. It provides a washable surface and is suitable for areas of high traffic such as reception areas, corridors, public areas, and any areas where high resistance to wear & tear is required. It can be applied on suitably primed woodwork and metal to provide a smooth low sheen finish.

SURFACE PREPARATION

New surfaces

Surfaces should be clean, dry and free of any loose and flaky materials before applying suitable primer and undercoat. Apply 2 coats of Ideal Eggshell Enamel.

Previously painted-sound surfaces

Abrade to achieve a slightly rough surface. Wipe & dust the surface and ensure that it is clean and dry. Apply 2 coats of Ideal Eggshell Enamel.

Previously painted-unsound surfaces

Remove all loose and flaky materials by scraping and wire brushing (if necessary) to a firm substrate. Clean & dust the surface and allow drying thoroughly. Seal the surface with 1-2 liberal coats of Ideal Penetrating Primer and allow to dry overnight. Apply 2-3 coats of Ideal Eggshell Enamel.

Where a colour change is required use one coat of Ideal Universal Undercoat followed by 1-2 coats of Ideal Eggshell Enamel.

FINISH

Semi gloss

APPLICATION

By brush, roller or spray.

THINNING AND MIXING

Thin with white spirit for brush or roller application and standard thinner for spray application.

EQUIPMENT CLEANING

Clean equipment immediately after use with white spirit.

DRYING TIME

Re-coatable after 16 hrs.

COLOUR RANGE

Brilliant White, BS 4800 Colour range, Ideal Classic Colour range & all NCS colours

SPREADING CAPACITY.

Approximately 11-14 m² per litre when applied on a primed or painted smooth surface.

PACK SIZES

1 litre, 4 litres & 20 litres.