

IDEAL RED/GREY OXIDE PRIMER

PRODUCT DESCRIPTION AND USES

Ideal Red/Grey Oxide Primer is a lead-free primer based on alkyd resin and iron oxide pigments. It can be applied on steelwork, commercial vehicle bodies, machinery, and metal casement, windows etc. Ideal Red/Grey Oxide Primer is tough and durable.

SURFACE PREPARATION

Surfaces to be painted must be completely dry and clean. Rust, grease and loose paint must be removed by wire brushing, scraping or sandblasting. Old Paint can be removed by using paint remover, while grease and oil can be removed by Ideal Special Thinner.

FINISH.

Matt

APPLICATION.

By brush or spray gun. Apply 2 coats of Ideal Red/Grey Oxide Primer giving an interval of 8 hours between coats. Slight sanding of the first coat is advisable before applying the second coat.

THINNING & MIXING.

Ideal White Spirit for brushing & spraying. Dilution: 4 parts paint to 1-2 parts white spirit

EQUIPMENT CLEANING.

Clean equipment immediately after use with white spirit.

DRYING TIME.

8 hours

COLOUR RANGE.

Red/Grey

SPREADING CAPACITY

12-14m² per litre at 40 microns DFT

PACK SIZES

1 litre, 4 litres & 20 litres