

IDEAL RED OXIDE ZINC CHROMATE METAL PRIMER

PRODUCT DESCRIPTION AND USES

An economical, general purpose metal primer formulated primarily for use on iron and structural steelwork. Based on an alkyd resin and pigmented with zinc chromate and red oxide pigments. Ideal Red Oxide Zinc Chromate Primer has excellent opacity and protects iron and steel surfaces against corrosion.

SURFACE PREPARATION

The surface to be primed must be clean and dry, free from oil, grease and dirt. All rust and mill scale must be removed by either mechanical means i.e. scraping and wire brushing, acid etching, grinding or by sand or short blasting. When using non-ferrous metals, such as aluminum, the surfaces must be primed first with an etching primer to enhance good adhesion.

Apply 1 liberal coat of Ideal Red Oxide Zinc Chromate Primer.

APPLICATION

Brush, roller or spray.

THINNING AND MIXING

Use Ideal White Spirit. Stir well before use. Dilution: 4 parts of paint to 1-2 parts white spirit.

EQUIPMENT CLEANING

Clean equipment immediately after use with white spirit.

FINISH

Matt.

DRYING TIME

Touch dry 4-6 hours. Recoatable in 10 hours.

COLOUR RANGE

Red

SPREADING CAPACITY

10-14m² per litre on smooth surface.

PACK SIZES

1 litre, 4 litres & 20 litres