



## **IDEAL ROADMARKING PAINT**

### **PRODUCT DESCRIPTION AND USES**

Ideal Road Marking Paint is manufactured especially for the painting of traffic lines for highways, streets, airports, factories, parking lots, playgrounds, etc. It has been formulated with a synthetic binder which dries rapidly and gives maximum resistance to wear and weather. The drying time varies from 5-15 minutes, depending on weather conditions and thickness of the applied layer.

Ideal Road Marking Paint provides a tough film with excellent adhesion to stone, asphalt, concrete etc.

### **SURFACE PREPARATION**

The surface must be clean and dry, free from any dust and loose bound materials.

### **FINISH**

Matt

### **APPLICATION**

By brush

### **THINNING AND MIXING**

Ideal Road Marking Thinner. Dilution - 4 parts paint to 1-2 parts thinner

### **EQUIPMENT CLEANING**

The equipment should be cleaned immediately with Ideal Road Marking Thinner.

### **DRYING TIME**

Surface dry 5-10 minutes.

Through dry 30-45 minutes at 25°C.

### **COLOUR RANGE**

White, yellow & black

### **SPREADING CAPACITY**

At normal film thickness a 4" strip approximately 4-5 m<sup>2</sup> per litre depending upon surface porosity.

### **PACK SIZES**

1 litre & 4 litres

### **PRECAUTIONS**

Ensure surface is free from gravel and dust

Never apply on wet surface. If after rain allow full drying before application.

Apply 2 coats allowing 30 minutes between coats. The first coat has to be thinned a little more for better adhesion.