

IDEAL TIMBERGUARD

PRODUCT DESCRIPTION AND USES

Ideal Timberguard wood protection is a decorative wood preservative which gives efficient protection to timber against insect and fungus attack, renders the surface water resistant and retains a natural appearance.

Ideal Timberguard gives excellent penetration into the surface providing effective protection for years against blue stain, rot or fungus as well as against insect attack. Timberguard may be used externally and internally on new or existing timber.

COLOUR AND EFFECT.

Timberguard is available as Clear and in light fast shades like Pine, Teak, Walnut, Ebony, Mahogany, Redwood, White etc.

On all timbers, the finished colour will depend on the type of timber, its colour, permeability and the number of coats of Timberguard applied. When in doubt it is recommended to carry out tests on the selected timber. Because of the natural darkening in colour of the timber, a certain change of each shade in the course of time must be taken into consideration.

DIRECTIONS FOR USE

Timberguard is supplied ready for use and should not be thinned. It is essential that pigmented Timberguard is thoroughly stirred before use and that it is kept stirred during application. The wood must be free from dirt and dust.

DRYING TIME

15-30 minutes after application of each coat, excess material should be lightly wiped off with a soft rag or brush.

SPREADING CAPACITY

6-12M² per litre dependent on the permeability and type of the timber.

PACK SIZES

1 litre & 5 litres

STORAGE

The container should be stored tightly closed.