

## **IDEAL ZINC CHROMATE PRIMER YELLOW**

### **PRODUCT DESCRIPTION AND USES**

Ideal Zinc Chromate Primer is a metal corrosion protection primer based on alkyd resin with zinc chromate as prime pigment. Ideal Zinc Chromate Primer is especially suitable for protection of iron and steelwork exposed to humid air and salt spray.

### **SURFACE PREPARATION**

Surfaces must be cleaned before priming. Sand blasting is recommended. Wire brushing may be used for small jobs where only mild corrosion is evident.

### **FINISH**

Matt

### **APPLICATION**

By brush or spray gun. Application of 1 coat of Ideal Zinc Chromate Primer, yielding about 35 microns DFT is recommended. Interval of 16 hours between coats must be allowed.

### **THINNING AND MIXING**

Use Ideal White Spirit for brush application and spray application. Dilution: 4 parts of paint to 1-2 parts white spirit.

### **EQUIPMENT CLEANING**

Clean equipment immediately after use with white spirit.

### **DRYING TIME**

Hard dry after 24 hours. Suitable for over coating after 16 hours.

### **COLOUR RANGE**

Yellow

### **SPREADING CAPACITY**

8-10 m<sup>2</sup> per litre at 35-40 microns DFT.

### **PACK SIZES**

1 litre, 4 litres & 20 litres